HP Latex R1000 Printer series



Help grow your business by printing high-value jobs on one device with white, rigid and flexible



Get amazing colors, rigid and flexible up to 64 in

- Move to higher value jobs with vibrant HP Latex gamut with media gloss and feel, and prints with no smell.³
- Simplify the workflow, get one look across rigid and flexible campaigns, and say goodbye to print and mount.
- Gain versatility with a single set of inks for scratch resistance and flexibility with HP Latex Overcoat.⁴

Expand with white, we've removed the barriers

- Glossiest white on transparent and colored media with high-opacity white that resists yellowing over time.²
- No waste between white jobs^s with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- Automatic maintenance makes white like any other color, including automatic recirculation and nozzle checks.

Manage your peaks in-house with smarter printing

- No need to outsource with high-speed quality up to 6.4 indoor/12 outdoor boards/hr⁶, continuous loading.
- Easy printing helps avoid costly mistakes with automatic maintenance, smart vacuum, and assisted loading.
- Maximize uptime with this smart printer for proactive and preventive services.

For more information, please visit http://www.hp.com/go/LatexRseries
Join the community, find tools, and talk to experts.
Visit the HP Latex Knowledge Center at http://www.hp.com/communities/LKC

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Most vibrant colors based on internal HP testing, January 2018 compared to leading competitive printers under \$350,000 USD. Tested in High Quality print mode on rigid (white acrylic 12-pass, 6-color, 120%). Internal HP testing with HP GamutViewer, Alpha Shapes=50000.

Clossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples. White ink capability may be optional, requiring purchase of the HP White Ink Option Kit.

³ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use

⁶ Indoor Production mode 6-pass, 110%. Outdoor mode 3-pass, 70%.

Technical specifications

| Printing modes 15 m²/hr - Indoor High Quality (12p 120%) 29 m²/hr - Indoor Production (6p 110%) 57 m²/hr - Outdoor (3p 70%) 12 m²/hr - White Overflood (100%) 28 m²/hr - White Spot (100%) 163 ft²/hr - Indoor Production (6p 110%) 311 ft²/hr - Indoor High Quality (12p 120%) 311 ft²/hr - Indoor Production (6p 110%) 590 ft²/hr - Outdoor (3p 70%) 131 ft²/hr - White Overflood (100%) 282 ft²/hr - White Spot (100%) 292 ft²/hr - White Spo | HP Latex Optimizer, 2 white) |
|---|----------------------------------|
| Ink types HP Latex Inks Ink cartridges 9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, F Cartridge size 3 L Printheads 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 L Long-term print-to-print Average s 1.0 dE2000, 95% of colors s 2 dE20002 repeatability Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of op | HP Latex Optimizer, 2 white) |
| Ink cartridges 9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, FC artridge size 3 L Printheads 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 L Long-term print-to-print Average s 1.0 dE2000, 95% of colors s 2 dE20002 repeatability Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of op | HP Latex Optimizer, 2 white) |
| Cartridge size 3 L Printheads 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 l Long-term print-to-print Average ≤ 1.0 dE2000, 95% of colors ≤ 2 dE2000 ² repeatability Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of op | HP Latex Optimizer, 2 white) |
| Printheads 8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 Long-term print-to-print Average ≤ 1.0 dE2000, 95% of colors ≤ 2 dE2000 ² repeatability Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of operations) | |
| Long-term print-to-print Average \le 1.0 dE2000, 95% of colors \le 2 dE2000 ² repeatability Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of operations) | |
| Media Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of operations) | ational outons in tables 1117 |
| Rigid media size 297 x 420 mm to 1625 x 1220 mm (up to 1625 x 3050 mm with two sets of op | ational oytoocion tables): /11.7 |
| | ational oytonsion tables): (11.7 |
| | |
| Thickness Up to 50.8 mm (Up to 2 in) | |
| Applications Exhibition and event graphics; Exterior signage; Interior decoration; POP/POS; S Vehicle graphics | hort-run packaging; Textile; |
| Connectivity | |
| Interfaces Gigabit Ethernet (1000Base-T) | |
| Dimensions (w x d x h) | |
| Printer 4.21 x 2.04 x 1.75 m (printer); 4.21 x 3.64 x 1.75 m (including standard input ar 69 in (printer); 166 x 143 x 69 in (including standard input and output tables)) | nd output tables) (166 x 80 x |
| Shipping 4.43 x 2.24 x 2.15 m (174 x 88 x 85 in) | |
| Operating area 6.61 x 6.03 x 3 m (21.7 x 19.8 x 9.8 ft) | |
| Weight | |
| Environmental ranges | |
| Operating temperature 15 to 30°C (59 to 86°F) | |
| Operating humidity 20 to 70% RH (non-condensing) | |
| Acoustics | |
| Power | |
| Consumption 8 to 10 kW (typical) | |
| Certification | |
| Safety IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD EN60950-1, EN12100-1, ENIS013849-1, EN60204-1, and EN1010-1); Russia, (EAC); Australia, New Zealand (RCM) | |
| Electromagnetic Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), (ACMA), New Zealand (RSM) | EU (EMC Directive), Australia |
| Environmental WEEE; RoHS (EU, China, Korea, Singapore, Turkey, Ukraine); India Waste Manage Prop; ErP Ecodesign Directive | ement Rules; REACH; CA 65 |
| Warranty 180-day limited hardware warranty. Warranty may vary by country as required http://www.hp.com/support to learn about HP service and support options in ye | |

Ordering information

| Product | |
|---------|-----------------------------|
| K0Q45A | HP Latex R1000 Plus Printer |

| Accessories | | | | |
|-------------------------------|--|--|--|--|
| T7V21A | HP Latex R1000 Extension Tables | | | |
| Y6V16A | HP Latex R Series Edge Holders Kit | | | |
| Original HP printing supplies | | | | |
| G0Z00A | HP 886 Latex Printhead Cleaning Kit | | | |
| G0Z01A | HP 872 3-liter Cyan Latex Ink Cartridge | | | |
| G0Z02A | HP 872 3-liter Magenta Latex Ink Cartridge | | | |
| G0Z03A | HP 872 3-liter Yellow Latex Ink Cartridge | | | |
| G0Z04A | HP 872 3-liter Black Latex Ink Cartridge | | | |
| G0Z05A | HP 872 3-liter Light Cyan Latex Ink Cartridge | | | |
| G0Z06A | HP 872 3-liter Light Magenta Latex Ink Cartridge | | | |
| G0Z07A | HP 872 3-liter Optimizer Latex Ink Cartridge | | | |
| G0Z08A | HP 872 3-liter Overcoat Latex Ink Cartridge | | | |
| G0Z09A | HP 886 3-liter White Latex Ink Cartridge | | | |
| G0Z21A | HP 886 White Latex Printhead | | | |
| G0Z22A | HP 886 Optimizer Latex Printhead | | | |
| G0Z24A | HP 886 Latex Printhead | | | |

Original HP large format printing materials

HP Premium Removable Gloss Adh

HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric (Recyclable)³

HP Backlit Polyester Film (Recyclable)³

Service and support 4BS24A/K0Q45-67270 HP Latex R Series Cleaning Kit 2WM39A/K0Q45-67267 HP Latex R Series Uptime Kit 2WM40A/K0Q45-67269 HP Latex R Series Expert Kit 2WP87A/K0Q45-67268 HP Latex R Series Reseller Kit

K0Q45-67272 HP Latex R Series Service Maintenance Kit K0Q45-67273 HP Latex R Series White Service Maintenance Kit G0Z00A/K0Q45-60840 HP Latex Printhead Cleaning Kit

Eco Highlights

- Better for print operations—no hazard warning labels or HAPs, no localized ventilation needed⁰¹
- $\bullet \quad \text{Better for the end-customer, more differentiation} \\ -- \text{odorless prints}^{02} \text{ go where solvent, UV}$ can't
- Better for the environment—HP designs end-to-end sustainability into large-format printing
- HP Latex Inks—UL ECOLOGO®/UL GREENGUARD GOLD Certified⁰³ and ECO PASSPORT certified⁰⁴

Please recycle large-format printing hardware and printing supplies. Find out how at our website

hp.com/ecosolutions

OT Contains no Hazardous Air Pollutants according to EPA Method 311. Localized ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Localized ventilation equipment installation is at the discretion of the customer—See the Site Preparation Guide for details. Customers should consult state and local requirements and regulations.

Of There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.

OF There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.











 $^{^{\}rm 1}$ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.

Reflective measurements on a 943 color target under CIE standard illuminant DSO. reflective measurements of a 342 color larget under the standard within and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. Backlit substrates measured in transmission mode may yield different results.

Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices, or can be returned through the HP Large Format Media take-back program. Recycling programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.